










NUEVAS CONFIGURACIONES AUTORIZADAS -ESCALABILIDAD Y BITRENES-

N°	TIPO DE VEHÍCULO	CONFIGURACIÓN N° DE EJES	LARGO	ANCHO	ALTO	PESO MÁXIMO (t)	Relación POT./PESO (CV/t) mín.
			(m)	(m)	(m)		
1		S1 - D2 - D3	18,60	2,60	4,30	49,50	6,00
2		S1 - D2 - D1 - D2	20,00	2,60	4,30	52,50	6,00
3		S1 - D1 - D2 - D2	20,00	2,60	4,30	52,50	6,00
4		S1 - D2 - D1 - D2	18,60	2,60	4,30	52,50	6,00
5		S1 - D2 - D1 - D1 - D1	18,60	2,60	4,30	55,50	6,00
6		S1 - D2 - D2 - D2	20,50	2,60	4,30	60,00	6,75
7		S1 - D2 - D2 - D2	22,40	2,60	4,30	60,00	6,75
8		S1 - D2 - D3 - D3	22,40 ≤ L < 25,50	2,60	4,30	75,00	6,75
9		S1 - D2 - D3 - D3	25,50 < L ≤ 30,25	2,60	4,30	75,00	6,75

○ Bitrenes